



# TECHNICAL DATA SHEET

## Age It

**Product Description:** **Age It** is a solvent based coating that is designed to give a blue or green patina the look that comes with age. It will take a new fresh green and age it 15-30 years so it dulls out a little and adds a little brown. Provided as a ready to use formula, it can be easily thinned with Solvent Thinner or Clear Guard if desired. Recoat time if needed is at least 1 hour. Age it is designed for use over a patina but it can be used on any metal or Metal Coating.

**Safety:** Use in a well ventilated area. Always wear goggles or face shield, vapor respirator, protective clothing and gloves when handling product. Store in temperatures between 50-90° F. Solvent Dyes will stain clothes, skin, and many other materials as well. **MIX WELL BEFORE USING.**

**Directions:** **Important Note:** Unseen moisture may be in the metal surface that will interfere with the Age It. Especially on humid days or earlier in the day, moisture will be undetectable to the bare eye. Trapped moisture will manifest itself as a cloudy coating and/or as a possible bonding problem. Oxidation, such as rust, can also develop over time. To prevent this, warm or heat the metal with a torch or heat gun prior to clear coating. If this is done, you should notice a shadow of water dissipate across the surface. Allow the metal to cool to room temperature for a few minutes, then proceed to with application.

1) Mix thoroughly before using.

2) Age It looks best when sprayed but it will adhere however you apply them to the surface, though they may show characteristics of application. Normal spray application will work well when using a 1.2 tip at about 18-25 psi from a HVLP sprayer or an air brush. It should look as though it is being atomized through a spray can. Allow 1 hour to dry between coats.

3) Reapply the Age It as needed to achieve the desired finish. Follow steps 2-4 as needed.

4) Warming the metal prior to clear coat can ensure that the unseen moisture is gone, do not use a flame for this. This step should not be necessary if you are clear coating shortly after Age It application, just ensure that you wait the minimum 1 hour wait time prior to applying the desired clear coat such as Clear Guard or Ever Clear.

**Before Using:** Please read, understand, and follow all the precautions shown on the product label and on the Safety Data Sheets. The Safety Data Sheets can be found on our website: [www.sculptnouveau.com](http://www.sculptnouveau.com)

### Technical Data

Physical State: Dark liquid

Ideal Application Conditions: 50-80°F

Coverage: About 300 sq ft/gal

Humidity: <50%

V.O.C.: <225lbs/gal

Clean Up: Solvent Thinner

Dry Time/Recoat Time: 1 hour

Phone: +760 432 8242  
Fax: 760 741 1074

Sculpt Nouveau, LLC  
1155 Industrial Ave  
Escondido, CA, 92029

E-Mail:  
[info@sculptnouveau.com](mailto:info@sculptnouveau.com)  
Website:  
[www.sculptnouveau.com](http://www.sculptnouveau.com)