



TECHNICAL DATA SHEET

Texture Paint

Product Description: **Texture Paint** is a water based product that allows the user to add incredible texture to the Metal Coating Process. Texture Paint is sold ready to use, though if desired it can be dried out or diluted to change the viscosity. Dilution should only be done with distilled water and allowing it to air dry is the best method to thicken it up. On non-metallic surfaces, you could apply the Texture Paint without the use of Prime It but it is still highly recommended to use Prime It first.

Safety: Use in a well ventilated area. Always wear goggles or face shield, vapor respirator, protective clothing and gloves when handling the product.

- Directions:**
- 1) Mix well prior to application.
 - 2) **If working on metal:** Clean the metal with Sculpt Nouveau Metal Cleaner and Degreaser and a Scotch-Brite pad, rinse with water after a few minutes. Sanding or sandblasting is recommended for the best adhesion. Cleaning the surface is mandatory after sanding or handling with bare hands.
 - 2) **If working on a non-metallic surface:** Ensure that the surface is clean from debris or contaminants **DO NOT** use Acetone or any solvent based cleaners.
 - 3) Apply 2 layers of the Prime It to the surface and allow this to dry overnight.
 - 4) Texture Paint can be applied in virtually any method you can think of that will give you the texture desired. The most common are often sponged on, brushed on, applied with a trowel or even ragged on. Thin coats are best, build up into thicker applications to avoid cracking.
 - 5) Allow the Texture Paint to fully dry at least 24 hours before using the Metal Coating over the top.

Before Using: Please read, understand, and follow all the precautions shown on the product label and on the Safety Data Sheets.
The Safety Data Sheets can be found on our website: www.sculptnouveau.com

Technical Data

Physical State: White

Recommended Thinner: Distilled water

Coverage: About 200 Sq. Ft. Per Gallon

Clean Up: Water

V.O.C.: Not applicable

Average Dry/Recoat Time: As soon as first coat is dry, minimum 1 hour

Flammability Limits: Not flammable

Handling and Storage: Mix well before using, keep closed when not using.

Phone: +760 432 8242
Fax: 760 741 1074

Sculpt Nouveau, LLC
1155 Industrial Ave
Escondido, CA, 92029

E-Mail:
info@sculptnouveau.com
Website:
www.sculptnouveau.com